



Plug with rubber coated coupling nut, short version

Series GB


Item number: GB603-24-28PN-EAC

Mechanical properties

Size:	24
Contact type:	Pin
Coding options:	4
Number of contacts, size 16:	24
Shell material:	Aluminum alloy
Surface treatment:	Epoxy-polyurethane
Type of surface:	varnished
Thickness of surface treatment:	13-16µ
Surface colour:	black
Corrosion resistance (h):	500
Operation temperature:	-55°C - +125°C
Temperature shock:	-55°C - +125°C
Conductivity (MΩ):	non conductive
EMI:	No
Material sealing ring:	Silicone
Coupling-torque to lock (Nm):	max. 6.5
Coupling-torque to open (Nm):	min. 2.0

Thermal properties

Material contact insert:	Ethylene acrylate GXF / thermoplastic
Operating temperature:	-55°C - +150°C
Fire protection class DIN EN 45545-2:	R23/HL3



Dimensional drawing

D1 (Ø):	58.0
L1 (mm):	36
N1:	1 3/8"-18 UNEF 2A
X1 (mm):	9

Electrical properties

Operating voltage DC (V):	250
Operating voltage AC (V):	200
Test voltage AC (V):	1000
Insulation resistance (Ω m):	≥ 5000
Insulation creepage distance (mm):	≥ 1.6
Voltage class:	MIL-DTL-5015

Electrical properties contacts

Size 16 - nominal current [continuous] (A):	13
Size 16 - maximal current [short-term] (A):	22
Size 16 - test current (A):	20

Complementary products:

Counterpart:



GB210-24-28SN-EAC
Receptacle, front panel mount

Backshell:



BEN24-AC
90° elbow back shell




BEN24-M5B-AC
90° elbow back shell with internal metric thread



BSH24-AC
Back shell with groove for heatshrinkable shapes



BSL24-AC
Backshell straight, long



BSN24-AC
Back shell straight, standard



BSN24-M5B-AC
Backshell straight with internal metric thread



BSR24-18-AC
Reducer back shell



BST24-AC
Termination back shell type R for grommets

Cable termination:



10-350349K-2432
Synthetic cable clamp

Contacts:




10-40557-05AU
Pin contact size 16, 0.25 -0.5mm²



10-40557-075AU
Pin contact size 16, 0.75mm²



10-40557-20-1AU
Pin contact size 16, 1.5mm²



10-40557AU
Pin contact size 16, 1.0mm²

Filler plugs:**10-101033-121**

Filler plug, size 16/16S

Protection cap:**PP24-AC**

Metallic protection cap to bayonet plug (GB,GR & GS)

**PP24-D**

Plastic protection cap to bayonet plugs (GB, GR & GS)