



Cable receptacle

Series GR

Item number: GR11-22-14PN-EAA


Packing unit: 1

Mechanical properties

Size:	22
Contact type:	Pin
Coding options:	2
Number of contacts, size 16:	19
Shell material:	Aluminum alloy
Surface treatment:	Zinc
Type of surface:	passivated
Thickness of surface treatment:	12-15μ
Surface colour:	black
Corrosion resistance (h):	200
Operation temperature:	-55°C - +90°C
Temperature shock:	-55°C - +125°C
Conductivity (MΩ):	≤ 0.5
EMI:	Yes
Coupling-torque to lock (Nm):	max. 6.0
Coupling-torque to open (Nm):	min. 1.5

Thermal properties

Material contact insert:	Ethylene acrylate GXF
Operating temperature:	-55°C - +150°C
Fire protection class DIN EN 45545-2:	R23/HL3



Dimensional drawing

D1 (Ø):	37.4
D2 (Ø):	40.0
L1 (mm):	34.3
L2 (mm):	19.0
L3 (mm):	4.0
N1:	1 1/4"-18 UNEF 2A
X1 (mm):	9.0

Electrical properties

Operating voltage DC (V):	700
Operating voltage AC (V):	500
Test voltage AC (V):	2000
Insulation resistance (Ω m):	≥ 5000
Insulation creepage distance (mm):	≥ 3.2
Voltage class:	MIL-DTL-5015

Electrical properties contacts

Size 16 - nominal current [continuous] (A):	13
Size 16 - maximal current [short-term] (A):	22
Size 16 - test current (A):	20

Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.

Voltage classes tested acc. MIL-DTL-5015

Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37

Corrosion resistance tested acc. MIL 1344A Test 101.1

Temperature shock tested acc. MIL 202F, 107G Method

Electrical conductivity acc. MIL 1344A, Test 3007

Complementary products:

Counterpart:



GR60-22-14SN-EAA

Plug with bayonet coupling nut



GR601-22-14SN-EAA

Plug with bayonet coupling nut, for EMI applications

Backshell:



BEN22-AA

90° elbow backshell




BEN22-M4B-AA

90° elbow backshell with internal metric thread



BSL22-AA

Backshell straight, long



BSN22-AA

Backshell straight, standard



BSN22-M5B-AA

Backshell straight with internal metric thread



BST22-AC

Termination back shell type R for grommets



ET-22-06-AA


EMI adapter with cone ring, for heatshrinkable shape

Contacts:



10-40557-05AU

Pin contact size 16, 0.25 - 0.5mm²



10-40557-075AU

Pin contact size 16, 0.75mm²



10-40557-20-1AU


Pin contact size 16, 1.5mm²



10-40557AU

Pin contact size 16, 1.0mm²

Filler plugs:



10-101033-121

Filler plug, size 16/16S

Protection cap:



PR22-AC

Metallic protection cap to bayonet receptacle (GB, GR & GS)



PR22-D

Plastic protection cap to bayonet receptacles (GB, GR & GS)