



Receptacle with threaded coupling, front panel mount

Series GT

Item number: GT210-20-19SN-EAC


Packing unit: 1

Mechanical properties

Size:	20
Contact type:	Socket
Coding options:	3
Number of contacts, size 8H:	3
Shell material:	Aluminum alloy
Surface treatment:	Epoxy-polyurethane
Type of surface:	varnished
Thickness of surface treatment:	13-16μ
Surface colour:	black
Corrosion resistance (h):	500
Operation temperature:	-55°C - +125°C
Temperature shock:	-55°C - +125°C
Conductivity (MΩ):	non conductive
EMI:	No
Coupling-torque to lock (Nm):	max. 5.0
Coupling-torque to open (Nm):	min. 1.5

Thermal properties

Material contact insert:	Ethylene acrylate GXF
Operating temperature:	-55°C - +150°C
Fire protection class DIN EN 45545-2:	R23/HL3



Dimensional drawing

D1 (Ø):	34.2
L1 (mm):	38.8
L2 (mm):	23.1
L3 (mm):	4.0
N1:	1 1/8"-18 UNEF 2A
N2:	1 1/4"-18 UNEF 2A
T1 (mm):	3.2
X1 (mm):	9.0
S1 (mm):	38.1
R1 (mm):	29.4

Electrical properties

Operating voltage DC (V):	700
Operating voltage AC (V):	500
Test voltage AC (V):	2000
Insulation resistance (Ω m):	≥ 5000
Insulation creepage distance (mm):	≥ 3.2
Voltage class:	MIL-DTL-5015

Electrical properties contacts

Size 8H - nominal current (A):	56
Size 8H - maximal current (A):	90
Size 8H - test current (A):	72

Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.

Voltage classes tested acc. MIL-DTL-5015

Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37

Corrosion resistance tested acc. MIL 1344A Test 101.1

Temperature shock tested acc. MIL 202F, 107G Method

Electrical conductivity acc. MIL 1344A, Test 3007

Complementary products:

Counterpart:



GT60-20-19PN-EAC

Plug with threaded coupling nut

Backshell:



BEN20-AA

90° elbow backshell



BEN20-M4B-AA

90° elbow backshell with internal metric thread




BSH20-AA

Backshell with groove for heatshrinkable shapes



BSL20-AA

Backshell straight, long



BSN20-AA

Backshell straight, standard



BSN20-M4B-AA

Backshell straight with internal metric thread



BST20-AA

Termination back shell typ R for grommet



ET-20-05-AA

EMI adapter with cone ring, for heatshrinkable shape

Contacts:



10-40796-18AG

Socket contact size 8H, 1.5mm²



10-40796-22AG

Socket contact size 8H, 2.5mm²



10-40796-38AG

Socket contact size 8H, 6.0mm²



10-40796-50AG

Socket contact size 8H, 10mm²

Filler plugs:



10-101033-141

Filler plug, size 8H

Accessory:



10-40450-20

Sealing gasket for receptacle, front panel mount



10-40450-20S

Sealing gasket for receptacle, front panel mount, conductive



10-40451-20

Sealing gasket for receptacle, rear panel mount



10-40451-20S

Sealing gasket for receptacle, rear panel mount, conductive