



Plug with threaded coupling nut

Series GT

Item number: GT60-10SL-3SN-EAC


Packing unit: 1

Mechanical properties

Size:	10SL
Contact type:	Socket
Shell material:	Aluminum alloy
Surface treatment:	Zinc
Type of surface:	passivated
Thickness of surface treatment:	12-15μ
Surface colour:	black
Corrosion resistance (h):	200
Operation temperature:	-55°C - +90°C
Temperature shock:	-55°C - +125°C
Conductivity (MΩ):	≤ 0.5
Coupling-torque to lock (Nm):	max. 1.7
Coupling-torque to open (Nm):	min. 0.45

Thermal properties

Material contact insert:	Ethylene acrylate GXF
Operating temperature:	-55°C - +150°C
Fire protection class DIN EN 45545-2:	R23/HL3



Dimensional drawing

D1 (Ø):	25.0
L1 (mm):	24.6
N1:	5/8"-24 UNEF 2A
N2:	5/8"-24 UNEF 2B
X1 (mm):	9.0

Electrical properties

Operating voltage DC (V):	700
Operating voltage AC (V):	500
Test voltage AC (V):	2000
Insulation resistance (Ω m):	≥ 5000
Insulation creepage distance (mm):	≥ 3.2
Voltage class:	MIL-DTL-5015

Electrical properties contacts

Size 16S - nominal current (A):	13
Size 16S - maximal current (A):	22
Size 16S - test current (A):	20

Please contact your Gimota partner for other shell materials, surface coatings or contact insert materials.

Voltage classes tested acc. MIL-DTL-5015

Power transmission verification acc. VG95234 / 2 test 5.10.1 and VG95210 / 37

Corrosion resistance tested acc. MIL 1344A Test 101.1

Temperature shock tested acc. MIL 202F, 107G Method

Electrical conductivity acc. MIL 1344A, Test 3007

Complementary products:

Counterpart:



GT210-10SL-3PN-EAC

Receptacle with threaded coupling, front panel mount

Backshell:



BEN10-M1B-AA

90° elbow backshell with internal metric thread




BSH10-AA

Backshell with groove for heatshrinkable shapes




BSL10-AA

Backshell straight, long




BSN10-AA

Backshell straight, standard



BSN10-M1B-AA

Backshell straight with internal metric thread



BST10-AA

Termination back shell typ R for grommet



ET-10-02-AA

EMI adapter with cone ring, for heatshrinkable shape

Contacts:



10-40552-05AU


Socket contact size 16S, 0.25 - 0.5mm²



10-40552AU

Socket contact size 16S, 0.75 - 1.5mm²

Filler plugs:



10-101033-121

Filler plug, size 16/16S