



# Contacts


**Pin contact K70C series, 70A, 25mm<sup>2</sup>**

**Item number: GMRC-PK70C-25AG**

**Packing unit: 5**

## Mechanical properties contacts

<b>Contact type:</b>	Pin
<b>Strand/wire adaptation:</b>	Crimp
<b>Number of mating cycles (min.):</b>	500
<b>Contact Material:</b>	CU alloy
<b>Protective layer:</b>	silver plated
<b>Wire section (mm<sup>2</sup>):</b>	25
<b>Stripping length (mm):</b>	15
<b>Max. Cable insulation Ø (mm):</b>	11



## Dimensional drawing

<b>D1 (Ø):</b>	6.0
<b>D2 (Ø):</b>	11.5
<b>D3 (Ø):</b>	10.0
<b>D4 (Ø):</b>	11.5
<b>d1 (Ø):</b>	7.0
<b>L1 (mm):</b>	35.0
<b>T1 (mm):</b>	15.5

## Electrical properties contacts

<b>Nominal current (A):</b>	70
-----------------------------	----



## Complementary products:

### Tools:



**B500ND**  
Hydraulic battery crimper B500ND - 18V



**HT51**  
Hydraulic press tool HT51 50kN



**MK-10-50**  
Hexagonal crimping dies for 50kN crimping tools, MK-10-50