



Module 17 pole, pin, 160V, 10A

Number of slots: 1

Item number: GMRM-160-10-17PZC-01


Packing unit: 1

Technical characteristics

Number of slots:	1
Number of contacts:	17
Contact type:	Pin
Number of mating cycles (min.):	500
REACH compliant:	SVHC substances, no
ROHS compliant:	Compliant

Thermal properties

Material contact insert:	Polycarbonate (PC)
Operating temperature:	-40°C - +125°C
Fire protection class UL94:	V0
Fire protection class DIN EN 45545-2:	R22/HL1,HL2 R23,24/HL1,HL2,HL3



Dimensional drawing

B1 (mm):	34.2
H1 (mm):	34.7
L1 (mm):	14.6

Electrical properties

Rated current (A):	10
Operating voltage (V):	160
Rated voltage acc. to UL/CSA (V):	250
Rated impulse voltage (kV):	2.5
Insulation resistance (Ω):	$\geq 10^{10}$
Pollution degree:	3



Complementary products:

Counterpart:



GMRM-160-10-17SZC-01
Module 17 pole, socket, 160V, 10A

Contacts:



GMRC-PDC-0.25AU
Pin contact DC series, 10A, 0.25mm²



GMRC-PZC-0.37AU
Pin contact ZC series, 10A, 0.37mm²



GMRC-PZC-0.50AU
Pin contact ZC series, 10A, 0.5mm²



GMRC-PZC-0.75AU
Pin contact ZC series, 10A, 0.75mm²



GMRC-PZC-1.0AU
Pin contact ZC series, 10A, 1.0mm²



GMRC-PZC-1.5AU
Pin contact ZC series, 10A, 1.5mm²



GMRC-PZC-2.5AU
Pin contact ZC series, 10A, 2.5mm²